

Eclipse Scout

Release Notes

Scout Team

Version 6.1

Table of Contents

Overview	1
What's New	1
Strong content security policy CSP	1
Enforcement of Model Thread	1
Properties support for Lists, Maps and imports	1
Binary resources support for HtmlField and BeanField	2
TriState capability for check boxes	2
New UriOpenAction: SAME_WINDOW	3
New methods in StringUtility	3
New ObjectUtility	3
Multiple Dimensions Support	3
Form Field	4
Enabled Inheritance	4
New Property "preventInitialFocus"	4
Menus in Tooltip	4
Table	5
New property "groupingStyle"	5
NumberColumn: new property "allowedAggregationFunctions", new aggregation type for no aggregation	5
UnloadRequestHandler for navigator.sendBeacon()	5
New annotation RemoteServiceWithoutAuthorization	6
Preparations for Scout JS	6
Button: new property 'defaultButton'	7
Icons for tree nodes	7
File Chooser Field: Improved Usability	8
Desktop Bench Layout configurable	8



Are you looking for the *Oxygen version* (2017) of the Eclipse Scout documentation? See the [7.0 version](#) of this document.

Overview

Eclipse Scout 6.1 is a preview of the Eclipse Oxygen release. The latest public build on this branch is *6.1.0.B006*. The official release for Eclipse Oxygen is Eclipse Scout 7.0 and will be released in June 2017.

- Download SDK: [Eclipse for Scout Developers](#)
- Runtime on Maven Central: [6.1.0.B006](#)

What's New

This document shows some of the new features delivered with the release 6.1. The release contains a lot of bugfixes and even some features not mentioned here. If you are interested in the detailed change log see <https://github.com/eclipse/scout.rt/compare/releases/6.0.x...releases/6.1.x>.

Strong content security policy CSP

The stronger CSP disables inline javascript in html. Therefore the 'New Scout Project' wizard now creates a js file per html file and includes it using the script element. To migrate existing projects, see the [Scout Migration Guide](#).

Enforcement of Model Thread

Every operation which results in a modification of the model and eventually of the ui has to be performed by the model thread. This has been true for a long time and still is. If the wrong thread was used, unexpected behavior was the result, like a delayed update of the ui or concurrency exceptions. To prevent such behavior in the future, an exception will be thrown if an operation is executed in the wrong thread.

If you get such an exception, you'll need to wrap your operation in a model job and schedule it using `ModelJobs.schedule()`, see the chapter ModelJobs in the [Scout Technical Documentation](#) for details.

Properties support for Lists, Maps and imports

Config properties support list- and map-data-structures. Furthermore other properties files can be imported. See the tech documentation section "[Configuration Management](#)" for more details.

Binary resources support for HtmlField and BeanField

Binary resources such as images or videos can now be used in the following widgets:

- HtmlField
- BeanField

Examples

BeanField

This is a BeanField

A BeanField is useful to display data in a custom way. The value of the field is a bean containing all the data relevant for presentation. Thus, compared to the HtmlField, the HTML itself is not delivered by the server but created on the browser using JavaScript and the raw data of the bean.

The header and description are part of the bean sent by the server. This is not necessary, you can access texts directly using javascript, like it is done for this text.

AppLinks are supported as well [Click me!](#)



Figure 1. Binary resource on a model field.

- Html enabled StringColumn
- BeanColumn



Image (Html enabled StringColumn)	Image (BeanColumn)	Name	↑	Size	Type	Date Modified
		bird.jpg		206 KB	JPG Image	01.01.70 00:59

Figure 2. Binary resource on a column

TriState capability for check boxes

Added support for tri-state value (**true**, **false** and **null** instead of just **true** and **false**) to boolean field and boolean column.

The new property **triStateEnabled** controls whether the boolean field/column behaves as a normal checkbox (**false**) or a tri-state checkbox (**true**).

A normal checkbox has values true/false. A tri-state checkbox has values true/false/null. The null value is interpreted as "undefined" and rendered as a filled square.

New UriOpenAction: SAME_WINDOW

The enum `UriOpenAction` provides a new value to open a URI in the current window: `SAME_WINDOW`

New methods in StringUtility

`StringUtility` provides the following new methods:

- `containsString()`
- `containsStringIgnoreCase()`
- `containsRegEx()`
- `matches()`
- `endsWith()`
- `startsWith()`
- `length()`
- `indexOf()`
- `lastIndexOf()`
- `split()` (with *limit* argument)

All methods are null-safe, unit tested and documented with JavaDoc.

New ObjectUtility

`ObjectUtility` was added as new utility for generic object methods and provides null-safe implementations of various Object methods. Various methods from former `CompareUtility`:

- `equals()`
- `notEquals()`
- `nvl()`
- `isOneOf()`
- `compareTo()`

And a new method `ObjectUtility.toString(Object)` providing a null-safe implementation of `Object.toString()` returning `null` if specified object is `null`.

Multiple Dimensions Support

Some components now support more dimensions for various attributes. E.g. until now there have been two dimensions for Form Field visibility: visible and visible-granted. Now there are also custom dimensions available. See the chapter 'Multiple Dimensions Support' in the [Scout Technical Documentation](#) for details and examples.

Currently the following attributes support multiple dimensions:

- Actions: visible, enabled

- Columns: visible
- Tree Nodes: visible, enabled
- Outlines: visible
- Form Fields: visible, enabled, label-visible
- Data Model Attributes: visible
- Data Model Entity: visible
- Wizard Steps: visible, enabled
- Trees: enabled
- Tables: enabled

Form Field

Enabled Inheritance

The inheritance of the enabled property for Form Fields has been changed. Now the enabled properties are no longer propagated to children if it is changed on a composite field. Instead a field is only considered to be enabled if itself and all of its parents are enabled. This allows to toggle an entire box to disabled and back to enabled without touching the child fields. This has the advantage that the original state is restored when the box is set back to enabled.

With this change the `getConfiguredEnabled` on composite fields now also automatically affects children. There is no need to overwrite `execInit()` and call `setEnabled(false)` anymore.

New Property "preventInitialFocus"

By default, the first enabled field on a form gets the focus when the form is opened. This may not be desired in some cases (e.g. if the first field is a HTML field that contains app links). The new property `PROP_PREVENT_INITIAL_FOCUS` can be used to prevent the initial focus to be set to this field. The default value is `false`. For `AbstractHtmlField` and `AbstractBeanField`, the default is set to `true`.

Menus in Tooltip

Form fields may have a tooltip and a context menu. Until now, it was not possible to display both simultaneously. This has been changed so that the menu items are now included in the tooltip if a tooltip text and menus are configured.




Figure 3. Tooltip with menus

Table

New property "groupingStyle"

The new property `groupingStyle` can be set to `bottom` (default) or `top`. Depending on the value aggregate rows are rendered on the bottom of grouped rows or on the top of grouped rows. The new top style can be set to have an aggregate row as a title for a group of table rows, this is useful for separating a table into multiple categories.

NumberColumn: new property "allowedAggregationFunctions", new aggregation type for no aggregation

The new property `allowedAggregationFunctions` can be set to any array of the aggregation functions `sum`, `avg`, `min`, `max` and `none` (default: all aggregation functions are allowed). It defines the allowed aggregation functions for this number column (e.g. a sum aggregation is not always useful for all number columns). Also a new aggregation type `none` was introduced, with the new type it is possible to remove an aggregation from a column which has previously been aggregated. For the new aggregation type no additional button has been introduced, if the new aggregation type `none` is enabled an aggregation which previously has been used can be removed by using the same aggregation button again.

UnloadRequestHandler for `navigator.sendBeacon()`

When a client leaves the application (e.g. puts `about:blank` in the address bar) one last "unload" request to the UI server is sent in order to properly clean up the session on the server.

If the browser supports the `Beacon API` `navigator.sendBeacon()` is used for this request. Unfortunately `application/json` is not a CORS-safelisted request-header which implies that we can't use the `JsonMessageRequestHandler` for the unload handling. Therefore a separate `UnloadRequestHandler` was introduced which handles all requests to `/unload/[UiSessionId]`. (For more information, see <https://git.eclipse.org/r/#/c/89422/>)

To cut a long story short, new traffic to `/unload` will be sent by the clients. Please check your

container and firewall configuration.

New annotation

RemoteServiceWithoutAuthorization

Remote services called through `IServiceTunnel` may whitelist authorization exclusions using this new annotation.

Preparations for Scout JS

A classic Scout application has a client model written in Java, and a UI which is rendered using JavaScript. With this approach you can write your client code using a mature and type safe language. Unfortunately you cannot develop applications which have to run offline because the UI and the Java model need to be synchronized.

With Scout JS this will change. You will be able to create applications running without a UI server because there won't be a Java model anymore. The client code will be written using JavaScript (or TypeScript) and executed directly in the browser.

This release (6.1) is the first step in this direction. Several actions have been performed:

1. Created `scout.App`

The new `App` object represents the *Single Page Application*. It will be initialized when the page loads and prepares all the necessary things the application needs to run, like texts, codes, fonts, logger and the session. These things may be different in case of a classic remote application and a Scout JS application. That is why there is another app called `scout.RemoteApp` which extends the `scout.App`. For you it basically means: if you create a Scout Classic App, use `scout.RemoteApp`, otherwise use `scout.App`.

2. Separated `Widget` and `Model Adapter`

A `ModelAdapter` is the connector with the server, it takes the events sent from the server and calls the corresponding methods on the widget. It also sends events to the server whenever an action happens on the widget. So if there is no server, there is no need for such adapters. This means in a Scout JS app you will only work with widgets, adapters are only required for remote apps.

3. Enhanced `Widgets`

With a Scout Classic app a lot happens on the UI server, like validating a form when the ok button is pressed. We started to enhance the JavaScript widgets with similar functionality and added API to use them. One example: The `ValueField` on Java side has a value and a display text. If a text is entered it will be parsed to get the value, or if a value is set the format function is called to get the text. This has not existed on JavaScript side, because the server only sent the text. This has been changed, parse and format functions now exist on the JS `ValueField` as well.

The preparations done in this release are just the first step. You could create a Scout JS app with this release, but a lot of the widgets are not ready to use yet. See also the [Scout Migration Guide](#) to migrate your existing JavaScript code.

Button: new property 'defaultButton'

A button may now be marked as default button which gives him a dedicated look to attract users attention. It will just change the look, the behavior stays the same.

Note: The first button or menu which has an **Enter** keystroke will automatically get that look too. This is existing behavior and hasn't changed. The new property has been added to give you more control, but actually you should always prefer the *enter keystroke approach* to provide a consistent behavior.

Icons for tree nodes

As in earlier Scout releases with Swing, SWT and RAP UI, the Outline and all Trees in Scout now support an icon per tree node. Simply set the `iconId` property on a `TreeNode` and reference either a character from an icon-font in your Scout project or a bitmap icon which is defined in your Scout project. See the migration guide for more details and the global property `showTreeIcons` which can turn on/off icons for all Tree instances. You should take care that all icons you use in a single tree have the same size. Here's an example for an outline with icons:




Figure 4. Outline with icons

File Chooser Field: Improved Usability

The file chooser field does not open an intermediate window anymore when clicked. Instead, the native file chooser is opened directly. This saves several clicks when a file needs to be uploaded. Furthermore, the whole field is now clickable. Until now the icon had to be clicked to choose a file which did not work well on touch devices.

Desktop Bench Layout configurable

The Desktop Layout can be configured using the `IDesktop.setBenchLayoutData` method. This property is observed and might be changed during the applications lifecycle. For more information take a look at the [Technical Guide](#).



Do you want to improve this document? Please [edit this page](#) on GitHub.